

In the Specification

On page 1, before the Title, kindly delete the following heading:

~~Description~~

Kindly replace paragraphs [0001] through [0007] with the following:

Related Application

This is a §371 of International Application No. PCT/JP2005/002148, with an international filing date of February 14, 2005 (WO 2005/080533 A1, published September 1, 2005), which is based on Japanese Patent Application No. 2004-045515, filed February 20, 2004.

~~Technical Field~~ Technical Field

The invention relates to a biomass gasification system and operating method thereof wherein a seal is formed to mutually separate and isolate the internal environments of a gasification furnace and thermal source, and a stable supply of a slag from the gasification furnace to the thermal source is obtained through a slag feed system.

~~Related Art~~ Background

A known biomass gasification system generates fuel gas through a process by which wood chips or poultry manure is thermally cracked in a non-oxidizing environment of a gasification furnace at temperatures from 600°C to 900°C. This system gasifies the combustible organic component of the biomass within a temperature range of from 200°C to 600°C. The fuel gas thus obtained is sent to an electrical generator powered by a combustion engine, gas engine, fuel cell, or other like fuel gas utilization device. This type of biomass-based electrical generating system has been looked upon with increasing interest during recent years.

Japanese ~~p~~Patent ~~a~~Application (No. 2003-155658) ~~for~~ discloses a biomass gasification system in which biomass is processed through the application of thermal energy from a thermal

source ~~in order~~ to generate a fuel gas. This system includes a slag supply system which feeds slag generated by the gasification furnace to the thermal source for use as a heat-generating fuel therein. Specifically, the slag supply system incorporates an extraction feeder connected with a slag extraction part of the gasification furnace and an insertion feeder provided between the extraction feeder and a slag insertion part of a thermal airflow generator as a thermal source. The former extracts the residual carbide (slag) generated by the gasification furnace in the biomass thermal treatment process, and the latter supplies the slag from the extraction feeder to the thermal airflow generator for use as such fuel therein. The slag supply system is thus able to sequentially feed the slag generated in the gasification furnace to the thermal airflow generator.

~~Disclosure of the Invention~~

~~Shortcomings Resolved by the Invention~~

Combustible fuel gas is generated within the internal environment of the gasification furnace, and exhaust gas, which includes combusted high temperature air for heating the gasification furnace, is generated in the internal environment of the thermal airflow generator. It is important that the respective internal environments of the gasification furnace and thermal airflow generator are mutually sealed off from one another. Therefore, a sealing mechanism must be provided in the slag supply system connecting the gasification furnace and thermal airflow generator in order to separate the respective environments. This sealing mechanism has taken the form of a damper or other like mechanical sealing device capable of appropriately opening and closing passages in the slag supply system so as to ensure both of seal and supply.

There are problems, however, ~~in that slag~~. Slag tends to build up and bridge across the passages of the slag supply system at locations where the mechanical seals have been installed, ~~and in that~~. Also, the components of the sealing mechanism tend to deform as a result of the heat of the

high-temperature slag. This is a phenomenon which adversely affects the reliable operation of the sealing mechanism.

Summary

This invention relates to a biomass gasification system in which thermal energy from a thermal source is applied to a gasification furnace to generate fuel gas, and in which a slag feed system is incorporated to supply slag generated in the gasification furnace to the thermal source for use as a heat-generating fuel therein including a slag holding part installed to the slag feed system and accumulating the slag.

This invention also relates to a biomass gasification system operating method applied to a biomass gasification system in which thermal energy from a thermal source is applied to a gasification furnace to generate fuel gas, and in which a slag feed system is incorporated to supply slag generated in the gasification furnace to the thermal source for use as a heat-generating fuel therein, including accumulating slag in a holding part installed to the slag feed system and forming a seal between internal environments of the gasification furnace and the thermal source.

Brief Description of the Drawings

Fig. 1 is a schematic diagram of a biomass gasification system.

Fig. 2 is a drawing describing how the electrical conductivity of slag is measured.

Fig. 3 is a graph illustrating the relationship between the airflow temperature and floor temperature of the thermal airflow generator during operation of the biomass gasification system.

Detailed Description

~~In response to the aforesaid shortcomings in the prior art, the inventor has construed~~We provide a biomass gasification system and operating method thereof wherein the internal environments of the gasification furnace and thermal source are mutually sealed off from one

another, and wherein a slag feed system provides a stable supply of slag from the gasification furnace to the thermal source.

~~Means of Overcoming Shortcomings in the Related Art~~

The ~~present~~ biomass gasification system ~~invention~~ applies thermal energy from a thermal source ~~in order to~~ generate fuel gas from biomass in a gasification furnace, and incorporates a slag feed system capable of supplying slag generated in the gasification furnace to the thermal source for use as a heat-generating fuel therein, and further incorporates a slag holding part in which the slag accumulates.

Kindly replace paragraphs [0009] through [0012] with the following:

A ~~detective means~~detector is provided to monitor the amount of slag in the holding part.

The ~~detective means~~detector is structured in the form of at least two electrodes which come into contact with the slag to form a conductive circuit.

~~Transport means~~A transporter is provided between the holding part and thermal source ~~in order to~~ transport slag from the holding part to the thermal source when the amount of slag, as monitored by the detective means, exceeds the amount required to form an environmental seal between the gasification furnace and thermal source.

[[A]]The biomass gasification system operating method ~~invention~~ applies thermal energy from a thermal source to a gasification furnace in which the thermal energy is used to generate fuel gas from biomass, and provides ~~means of feeding a~~slag feeder for slag generated in the gasification furnace to the thermal source for use as a heat-generating fuel therein. The operating method includes a step that the slag accumulating in the holding part installed to the slag feed system forms a seal which mutually isolates and separates the internal environments of the gasification furnace and thermal source.

Kindly replace paragraphs [0014] through [0017] with the following:

Effect of the Invention

The biomass gasification system and operating method invention appropriately seals and separates the internal environments of the gasification furnace and thermal source, and is able to provide a stable supply of slag from the gasification furnace to the thermal source through the slag feed system.

Preferred Embodiments of the Invention

The following description provides a detailed description of ~~an embodiment~~ a selected, representative example of the biomass gasification system and operating method thereof ~~invention~~ with reference to the attached drawings. The biomass gasification system ~~invention~~, as described herein this embodiment and illustrated in Fig. 1, includes a slag feed system 3 which supplies slag S to a thermal source, in this case thermal airflow generator 1, for use as a heat-generating fuel therein, ~~said~~ the slag S having been generated as a residual component of the process where the thermal airflow from the thermal airflow generator 1 is applied to wood chips or other biomass material to be cracked into a fuel gas. The slag feed system 3 also includes a vertical hopper 4 as a holding part in which slag S accumulates.

The gasification furnace 2 is a dual-chamber structure comprising a gasification chamber 2a into which biomass is placed and subjected to a heating process ~~in order to~~ generate fuel gas, and an external thermal chamber 2b formed around the periphery of gasification chamber 2a as means of applying energy thereto for executing the heat process. Thermal airflow generator 1 operates by combusting a fossil fuel or slag S which is supplied from the gasification furnace 2 ~~in order to~~ generate a thermal airflow of exhaust gas containing high temperature air. The thermal airflow generated by the thermal airflow generator 1 heats the gasification chamber 2a of the gasification

furnace 2 by flowing through the external thermal chamber 2b from where it is blown back to the thermal airflow generator 1 by a thermal circulation fan 5. A slag discharge part 2c is installed to the gasification chamber 2a of the gasification furnace 2 as means of discharging slag S which is carbide generated by the biomass thermal cracking process. Slag insertion part 1a is provided with the thermal airflow generator 1 to supply slag S thereto.

The slag feed system 3, which is installed between slag discharge part 2c of the gasification furnace 2 and slag insertion part 1a of the thermal airflow generator 1, transports slag S from the gasification furnace 2 to the thermal airflow generator 1 at a temperature above 350°C. The slag supply system 3 includes extraction means ~~in the form of a~~such as extraction screw feeder 6 powered by motor 6a, and transport means ~~in the form of a~~such as insertion screw feeder 7 powered by motor 7a. The feeders 6 and 7 are enclosed within a hermetically sealed cover 8. The extraction screw feeder 6 is approximately horizontally disposed, and includes a collector end 6b connected to slag discharge part 2c of the gasification furnace 2 and an export end 6c to which the discharged slag S from the gasification furnace 2 is sent by feed operation. The insertion screw feeder 7 is in inclined disposition with its upper discharge end 7b connected to slag insertion part 1a of the thermal airflow generator 1, and its lower receiver end 7c disposed beneath the export end 6c of the extraction screw feeder 6. The insertion screw feeder 7 transports slag S, which has been supplied by the extraction screw feeder 6 to the receiver end 7c, to the thermal airflow generator 1.

Kindly replace paragraphs [0020] through [0021] with the following:

~~Detection means~~A detector, in the form of electrically conductive electrodes 9, 10 and 11, ~~are~~is installed to the vertical hopper 4 and ~~are~~in contact with slag S therein ~~in order to~~ monitor the slag volume, that is to say, the height of slag S[[,]] accumulated within the vertical hopper 4. Slag S is a particulate substance which may have a particle diameter ranging from 1 to 10mm. If the

biomass raw material consists of wood chips, elemental analysis of the resulting slag S reveals, as shown in Table 1, that 88% of the composition is electrically conductive carbide. As shown in Fig. 2, an electrical circuit tester 12 reveals that such slag S has approximately 5,000 Ohms of resistance when measured over a 100mm span, thus indicating a substantial amount of electrical conductivity.

{Table 1}

	Unit of measurement	Combusted Sample	
		wood chips	Carbide
Sodium	%	0.036	0.031
potassium	%	0.15	0.87
all chlorines	%	0.39	0.39
Carbon	%	46	88
Hydrogen	%	6.1	less than 0.1
Nitrogen	%	0.2	0.2
combustible sulphur	%	0.19	0.05
gross caloric value	MJ/kg	19.2	31.5
water component	%	64	2.5
volatile component	%	83.5	4.5
ash component	%	0.3	2.7
Oxygen	%	46	9.2
combustible component	%	35	94
solid oxygen	%	16.2	92.8
all sulphurs	%	0.22	0.07
combustible chlorine	%	less than 0.01	0.04

Table 1: Carbide slag from wood chips

Electrodes 9, 10 and 11, which ~~are~~may be made of stainless steel, are disposed to penetrate the walls of the vertical hopper 4, and are electrically insulated from the hopper walls by encapsulation within insulators 13. Three electrodes 9, 10 and 11 are illustrated and used in this ~~embodiment~~example, although other numbers of electrodes may be employed. The first electrode 9

is installed at the top end of the vertical hopper 4, the second electrode 10 is installed to the vertical hopper 4 below the bellows duct 4c at a height establishing the volume of slag S required to form an effective seal, and the third electrode 11 is installed below the second electrode 10 and above the receiver end 7c of the insertion screw feeder 7 at a height which establishes the minimum volume of slag S required to form the seal. A wire lead 14 is attached to each electrode 9, 10 and 11, and also to lower hopper 4b.

Kindly replace paragraph [0025] with the following:

While the biomass gasification system is operating, the height of accumulated slag S in the vertical hopper 4 is monitored by ~~detection means in the form of~~detectors such as electrodes 9, 10 and 11. A small amount of electrical current is applied by the electrical power source 15 to the wire leads 14 connected to the electrodes 9, 10 and 11 and the lower hopper 4b. The control unit 16 is able to recognize a conductive or insulated state between each electrode 9, 10 and 11 and the lower hopper 4b, the conductive or insulated state being determined by the accumulated slag S respectively contacting or not contacting the electrodes 9, 10 and 11.

Kindly replace paragraph [0028] with the following:

Furthermore, when the insertion screw feeder 7 is running at a slow speed with the second electrode 10 in a insulated state (and the third electrode 11 in a conductive state), the control unit 16 will output a “stop” signal to the motor 7a ~~in order to~~ terminate operation of the insertion screw feeder 7 as a means of preventing the height of the accumulated slag S from reaching the third electrode 11 which establishes the minimum allowable slag height. When the second electrode 10 returns to a conductive state (with the third electrode 11 also in a conductive state), the control unit 16 will output a signal to the motor 7a to re-start the insertion screw feeder 7 at a low speed to resume the transport of slag S to the thermal airflow generator 1.

Kindly replace paragraphs [0030] through [0031] with the following:

The biomass gasification system and operating method thereof, as described in this ~~embodiment~~example, utilizes a holding part, in the form of the vertical hopper 4, which is installed to slag feed system 3. The accumulation of slag S in the vertical hopper 4 provides a sealing function able to mutually separate and isolate the internal environments of the gasification furnace 2 and thermal airflow generator 1. Compared to a mechanical sealing structure wherein slag S forms a bridge across the installation region of such sealing structure, and wherein thermal distortion of the mechanical sealing structure adversely affects its operation, the utilization of only accumulated slag S in the vertical hopper 4 to seal off the internal environment of the gasification furnace 2 from that of the thermal airflow generator 1 eliminates the need for a mechanical sealing component. An extremely simple and extremely reliable sealing structure is thus obtained. In respect to the method wherein slag S is supplied to the thermal airflow generator 1 from the gasification furnace 2, the slug feed operation through which the slag feed system 3 allows slag S to temporarily accumulate within the vertical hopper 4 while concurrently supplying slag to the thermal airflow generator 1 proceeds in a highly stable manner without any adverse affects on the effectiveness of the seal formed by slag S.

The pressures within the gasification furnace 2 and thermal airflow generator 1 are separately controlled to a pressure differential within about 200Pa. For example, if the specific gravity of slag S is 0.113 and slag S has been accumulated within the vertical hopper 4 to a height of 354mm, the sealing function may be maintained up to a pressure differential of about 400Pa.

Kindly replace paragraphs [0033] through [0037] with the following:

This ~~embodiment specifies detective means in order~~example includes a detector to detect the volume of slag S within the vertical hopper 4, therefore making it possible to accurately comprehend the amount of slag S accumulated therein. Knowing the height of slag S in the vertical hopper 4

enables automatic or manual control of the slag feed system 3 ~~in order~~ to maintain the volume of slag S at a ~~required~~specified height which provides the sealing function, and to enable an appropriate supply of slag S from the gasification furnace 2 to the thermal airflow generator 1.

The detection value provided by the detective means is applied to enable automatic operation of the biomass gasification system, particularly the automatic operation of the insertion screw feeder 7. ~~In this embodiment, the~~The control unit 16 utilizes the conductive or insulated states of the electrodes 9, 10 and 11 to automatically control operation of the insertion screw feeder 7 through the motor 7a in order to maintain a level of slag S in the vertical hopper 4 sufficient to provide the required sealing function, and to appropriately control the supply of slag S to the thermal airflow generator 1.

In other words, ~~in this embodiment,~~ the switching point at which the operation of the insertion screw feeder 7 starts or stops is based on the amount of slag S in the vertical hopper 4. The point in time at which the level of slag S rises above the second electrode 10 is monitored, that is, the point in time is detected at which the second electrode 10 assumes a conductive state indicating that the required environmental seal has been established. This operation thus enables the supply of slag S from the vertical hopper 4 to the thermal airflow generator 1 to be executed in a manner which an appropriate supply of slag S is maintained ~~under assuring~~to assure an adequate sealing function.

Moreover, the ~~detective means~~detector, which is structured from the conductive electrodes 9, 10 and 11 which penetrate the wall of vertical hopper 4, and from the lower hopper 4b which also functions as an electrode, utilizes the conductivity of slag S. Therefore, the amount of slag S within the vertical hopper 4 may be externally grasped even with the temperature of the slag S being in excess of 350°C. Furthermore, the ~~detective means~~detector operates with a high level of reliability

due to its simple structure comprising ~~only~~ the electrodes 9, 10 and 11, even though they are installed to the vertical hopper 4 in which slag S is cast.

Moreover, ~~the~~ installation of electrodes 9, 10 and 11 at points of three levels within the vertical hopper 4 enables ~~the~~ detection of three different slag heights through which operation of the insertion screw feeder 7 is controlled. Thus, ~~an extremely~~ a fine level of control may be established.

Kindly replace paragraphs [0039] through [0040] with the following:

While the preceding description ~~of the embodiment~~ refers to the holding part structured in the form of the vertical hopper 4, the holding part may also be structured in other ways such as a horizontal hopper, when the extraction screw feeder 6 as a push-in type feeder which pushes slag horizontally into the hopper is used and the amount of slag S is detected along the length of the horizontal hopper. Of course, a slant hopper or other shapes/orientations may be used. Moreover, the power source 15 may be installed to each electrode 9, 10 and 11.

Brief Description of the Drawings

~~Fig.1 is a schematic diagram of a preferred embodiment of the biomass gasification system invention.~~

~~Fig. 2 is a drawing describing how the electrical conductivity of slag is measured.~~

~~Fig. 3 is a graph illustrating the relationship between the airflow temperature and floor temperature of the thermal airflow generator during operation of the biomass gasification system.~~